

## p: 877.283.4852/563.927.4900 | xlspecializedtrailer.com 1086 South 3rd St | Manchester, IA 52057



## YOUR SOLUTIONS-BASED HAULING PARTNER



## SUPERIOR HYDRAULICS

The XL Slider features an extended dump angle of 17 degrees and improved hydraulics to keep your equipment from unnecessary wear. Hydraulic sliding axle assembly with traveling bumper provides under ride protection.



## **UNMATCHED EFFICIENCY**

A 6½ degree load angle permits you to easily load pavers and rollers, while the winch at the front loads inoperable equipment. A single 2 stage cylinder provides maximum travel and minimal maintenance.



## **USER-FRIENDLY FEATURES**

Haul forklifts with the durable 4-inch and 3" Jr. I-beam crossmembers on 8-inch centers. Enjoy new standard features: chain slots down the outer and center beams, a 2-function wireless remote, and Teflon coated rollers that do not need to be greased.

## **BUILT WITH YOU IN MIND**


- Available in 48', 51' and 53' OAL
- California legal and R-tac legal specs available
- Chain drops down the outer beams and double chain drops down the center
- 17° dump angle
- Two speed landing gear
- 20,000 lb winch with 100' of %6" cable comes standard
- Teflon coated rollers do not need to be greased
- 21" king pin setting
- 2 recessed cable rollers
- 10' 5" full-width upper deck
- All XL Specialized Trailers' products go through the new, premium paint process. XL paint includes a full 1 year warranty.
- XL Specialized Trailers' Slide Axle trailers feature a 5 year structural warranty.

## FIND YOUR SPECIALIZED SOLUTION TODAY visit xlspecializedtrailer.com



## p: 877.283.4852/563.927.4900 | xlspecializedtrailer.com 1086 South 3rd St | Manchester, IA 52057

# **XL SLIDE AXLE**



## XL 80 SA

CAPACITY: 80,000 LB OVERALL CONCENTRATED: 50,000 LB IN 10' OAL: 48', 51' OR 53' | OAW: 102"

SPECS

#### **UPPER DECK**

10' 5" FULL WIDTH NECK 49" 5TH WHEEL HEIGHT 82" SWING CLEARANCE 21" KING PIN SETTING 13/8" RAISED APITONG DECKING 2 TOOL BOXES IN UPPER DECK WITH STEEL DOORS 1 RECESSED CABLE ROLLER, BACK OF NECK CHAIN DROPS ON 48" CENTERS, BOTH SIDES HYDRAULICS RUN OFF OF WET KIT HYDRAULIC CONTROL LEVERS 2 SPEED LANDING GEAR 20,000 HYDRAULIC WINCH WITH MANUAL KICKOUT, & 100' WITH %16" CABLE WITH LOOP, PLANETARY DRIVE **2 FUNCTION WIRELESS REMOTE** 

#### UPPER DECK OPTIONS

5TH WHEEL HEIGHT OTHER THAN 49" 28HP HONDA SELF-CONTAINED POWER UNIT WITH DUAL HYDRAULICS MARK V 2 SPEED LANDING GEAR HYDRAULIC PARK STANDS 15,000 LB HYDRAULIC PLANETARTY DRIVE WINCH WITH 1/2" CABLE & LOOP 30,000 LB HYDRAULIC PLANETARY DRIVE WINCH WITH %6" CABLE & LOOP AIR KICKOUT FOR WINCH 6 FUNCTION WIRELESS WINCH REMOTE CONTROL 7 FUNCTION WIRELESS REMOTE, FOR USE WITH AIR KICKOUT OPTION 10 FUNCTION WIRELESS REMOTE, FOR USE WITH AIR **KICKOUT & DOCK LEVELERS** REGISTRATION HOLDER

## SUSPENSION

25,000 LB AIR RIDE MANUAL DUMP VALVE

#### SUSPENSION OPTIONS

LIQUID FILLED AIR GAUGE AIR WEIGH DIGITAL SCALE

### MAIN DECK

T-1 FLANGE, 80K WEB FAB I-BEAM (4 BEAM TRAILER) 38" LOADED DECK HEIGHT 1 RECESSED CABLE ROLLER IN FRONT 1¾" RAISED APITONG DECKING 4" JR. I-BEAM & 3" I-BEAM ON 8" CTRS CHAIN DROPS ON 24" CENTERS, EACH SIDE DOUBLE CHAIN DROPS DOWN THE CENTER

ENERGY CHAIN TO PROTECT AIR, ELECTRIC, AND HYDRAULIC LINES 6½° LOAD ANGLE 48' OAL: 17° DUMP ANGLE 51' OAL: 16° DUMP ANGLE 53' OAL: 15° DUMP ANGLE

#### MAIN DECK OPTIONS

9'WIDE 10'WIDE DOCK LEVELERS STAKE POCKETS ALT. W/ CHAIN SLOTS ON 12" CENTERS, OUTER BEAMS ADDITIONAL BENT D-RINGS PAN-STYLE D-RINGS DROP DOWN D-RINGS AMBER STROBE AS THIRD TAILLIGHT

## WHEELS AND TIRES

6.75 X 17.5 STEEL RIMS 245 / 70R / 17.5 TIRES

#### WHEELS AND TIRE OPTIONS

235/75R/17.5 TIRES 245/70R/17.5 MICHELIN TIRES 255/70R/22.5 16PR RADIAL (DECK HEIGHT + 4.5") PSI TIRE INFLATION SYSTEM ALUMINUM MILL WHEELS ALUMINUM POLISHED WHEELS ALUMINUM DURABRIGHT WHEELS

#### AXLES

(2) 25,000 LB NOMINAL 50" SPACING HUB PILOT, OUTBOARD DRUMS 12¼" X 7½" BRAKES AUTO SLACK ADJUSTERS LIMIT CHAINS ON ALL AXLES 2S1M SPRING BRAKES ON 1 AXLE GREASELESS ROLLERS ON SLIDING AXLE ASSEMBLY

#### **AXLE OPTIONS**

60" AXLE SPACING CHASSIS UNI LUBE SYSTEM CAM COVERS HUBOMETER DUST SHIELDS SPRING BRAKES ON 2ND AXLE

## LIGHTING

D.O.T. APPROVED 12V SEALED GROTE HARNESS RUBBER MOUNTED LED LIGHTS (1) MID-TURN SIGNAL PER SIDE (2) CLEARANCE LIGHT PER SIDE 7 POLE ELECTRICAL SOCKET 2 TAIL LIGHT PACKAGE WITH ALUMINUM COVER

## PAINT

1 YEAR WARRANTY BLACK, IH RED, OR NEW CAT YELLOW AIR & ELECTRIC DONE AFTER PAINT

## **AVAILABLE MODELS**

XL 80 SA XL 80 SA: CALIFORNIA LEGAL XL 80 SA: R-TAC LEGAL XL 110 SA

OTHER CUSTOM CAPACITIES AND OPTIONS ALSO AVAILABLE, ASK YOUR SALES REP FOR DETAILS