45 ton *(40.8 mt)* Telescopic Crawler Crane

AN IN

15

- Remarkable control, reliability &

][

Remarkable control, renability of capacity performance
Wireless rated capacity limiter
Unbeatable hydraulic pilot-operated control
Fits in places no other rough terrain nor crawler can
Quick mobilization

(C)

C R A N E

С

S

Quick mobilization – transports in one load

45-ton *(40.8 mt)* Telescopic Crawler Crane

Remarkable control, reliability and capacity performance

- Whisper quiet **Isuzu engine** with 197 hp (146.90 kW)
- Matching drums grooved for 18mm wire rope with 17,916 lbs (8 127 kg) available line pull
- Mechanical drum rotation indicators
- 340 fpm (103.7 m/min) line speed
- Optional auxiliary lifting sheave off main boom



4-section full power boom with attachment flexibility

- Full power 33 ft to 105 ft (10.06 m to 32.0 m) four-section boom
- Exclusive A-max mode offers substantially increased capacities in close. Standard "B" mode extends all four sections equally.
- Maximum boom/jib length is 105 ft + 20 ft(32 m + 6.09 m)
- Lightweight nylon head sheaves reduce overall machine weight and increase lift capacities
- Quick reeve boom head allows rope to be easily reeved over boom head
- Hammerhead boom nose allows operator to work at high boom angles
- Optional 20 ft (6.09 m) one-piece swing-away fly



Ergonomically designed for maximum visibility, comfort and control

- Wireless rated capacity limiter
- Sliding left side door, right and rear windows, and swing up top window provide excellent ventilation
- AM/FM radio
- Air conditioner / hot water heater
- Hand and foot throttle
- Travel pedals
- Single axis controls

32" grouser track shoes form a wide gauge of 11' 2" (3.40 m) when extended, and 8' 9" (2.66 m) when retracted with two position house lock.







Quick mobilization & superb job-site mobility

- Transports COMPLETE ONE LOAD
- Fold-up catwalks
- Hydraulic retractable side frames for transport



Link-Belt Construction Equipment Company Lexington, Kentucky www.linkbelt.com

® Link-Belt is a registered trademark. Copyright 2007. All rights reserved. We reserve the right to change designs and specifications at any time. Litho in U.S.A. 6/10 536 #4379 (supersedes #4340)