



RTC-8090

Kelly Tractor Co. offers Florida's premier solution for your lifting needs. As an authorized dealer for Link-Belt cranes, we provide the full compliment of construction cranes.

Our dedicated sales and support staff consists of the most experienced professionals in the industry. Our objective is to meet and exceed all of your crane needs with the highest quality products backed by the best parts and service team in the business. Whether you are in the market to purchase or simply rent, Kelly Tractor Co. is the best choice.

SE Florida - Julio Rivas - Phone: (305) 613-1571

NE Florida - Hugo Verez - Phone: (407) 399-1248 - Se Habla Español

West Coast Florida - Bill Hershner - Phone: (941) 350-9023

Parts (561) 683-2015 Extension 104

Rough Terrain Cranes

Models	Capacity US t (mt)	Boom type & Length ft (m)	Maximum Tip Height ft (m)	Operating Weight (lbs) kg
RTC-8030 II	30 (30)	4-Section 29-91.4 (8.8-27.8)	143 (43.6)	55,600 (25 220)
RTC 8050 II	50 (50)	4-Section 35.6-110 (11.6-35)	168 (51.2)	72,700 (32 976)
RTC 8065 II	65 (60)	4-Section 38-115 (11.6-35)	211.6 (64.5)	84,000 (38 600)
RTC 8080 II	80 (80)	4-Section 38-64 (11.6-19.5)	230.8 (70.4)	87,123 (39 518)
RTC 8090 II	90 (80)	5-Section 38-140 (11.6-42.7)	238 (72.5)	99,100 (44 951)
RTC 80110II	110 (100)	5-Section 40-150 (12.2-45.7)	250 (76.2)	129,442 (58 714)
RTC 80130 II	130 (120)	5-Section 41.3-162 (12.6-49.3)	278 (84.7)	130,589 (59 234)

Hydraulic Truck Cranes

Models	Capacity US t (mt)	Boom type & Length ft (m)	Maximum Tip Height ft (m)	Operating Weight (lbs) kg	Engine Type & HP (kW)
HTC-8640 SL	40 (36.2)	4-Section 35.6-110 (10.8-33.5)	167 (50.9)	65,605 (29 758)	Cummins ISL9 365 (272)
HTC-8660 II	60 (50)	4-Section 35.6-110 (10.8-33.5)	167 (50.9)	72,769 (33 007)	Cummins ISL9 365 (272)
HTC-8675 II	75 (70)	4-Section 41-127 (12.5-38.7)	230 (70.2)	85,276 (38 681)	Cummins ISX12 450 (336)
HTC-8690 II	90 (81.6)	5-Section 38-140 (11.6-42.7)	237 (72.2)	91,086 (41 316)	Cummins ISX12 450 (336)
HTC-86100	100 (85)	5-Section 38-140 (11.6-42.7)	237 (72.2)	91,086 (41 316)	Cummins ISX12 450 (336)
HTC-3140	140 (120)	5-Section 41.4-162 (12.6-49.3)	278 (84.7)	103,414 (46 908)	Cummins QSB-6.7 250 (185)
HTC-3140 LB	140 (120)	6-Section 42.3-195.3 (12.8-59.5)	311 (94.7)	108,618 (49 268)	Cummins QSB-6.7 250 (185)



Telescopic Crawler

Models	Capacity US t (mt)	Boom Type and Length ft (m)	Height Width Length ft (m)	Engine Type & HP (kW)	Gradeability	Operating Weight lb (kg)	Track extended gauge & length ft (m)
TCC-500	50 (51)	4-Section 35.6-110 (10.8-33.6)	H: 9.10 (3.01) W: 11.5 (4.12) L: 45.3 (13.85)	Cummins QSB 215 (160) Tier 4f	40%	97,600 (44 225)	Gauge: 11 (3.35) Length: 18 (5.47)
TCC-750	75 (70)	4-Section 38.6-115.6 (11.8-35.2)	H: 10.9 (3.29) W: 11.5 (3.63) L: 48.9 (14.35)	CAT C6 262 (195) Tier 3	40%	100,000 (45 359)	Extended: 15.2 (4.63) Intermediate: 13.6 (4.12) Track Length: 19.6 (5.95)
TCC-1100	110 (100)	5-Section 40-150 (12.2-45.7)	H: 11.8 (3.60) W: 11.9 (3.62) L: 48.6 (14.81)	Cummins QSL 320 (239) Tier 4	40%	221,500 (100 47 1)	Extended: 15.18 (4.63) Intermediate: 12.73 (3.88) Retracted: 8.9 (2.73) Track Length: 23.35 (7.12)

All Terrain Cranes

Models	Capacity US t (mt)	Boom type & Length ft (m)	Maximum Tip Height ft (m)	Operating Weight (lbs) kg	Upper Engine Type & HP (kW)
ATC-3210	210 (185)	6-Section	326.7 (99.6)	125,585 (55 603)	Cummins 215 (160)
ATC-3275	275 (250)	7-Section	350 (106.7)	136,000 (61 688.5)	Cummins 215 (160)

Lattice Crawler Cranes

Models	Capacity US t (mt)	Crane Operating Weight lb (kg)	Boom Type & Length ft (m)
138 HSL	80 (73)	145,403 (65 954) Counterweights "ABC"	Tube: 40-200 (12.19-60.96) Angle: 40-150 (12.19-45.72)
218 HSL	110 (100)	192,735 (87 423)	Tube: 40-230 (12.19-70.10)
238 HSL	150 (137)	262,677 (119 148) Counterweights "ABC"	Tube: 50-260 (15.24-79.25)
248 HSL	200 (182)	270,130 (122 529)	Tube: 55-285 (16.76-86.86)
298 HSL	250 (227)	390,069 (176 932)	Tube: 60-300 (18.29-91.44)
348 Hylab 5	300 (273)	505,688 (229 376)	Tube: 70-300 (21.3-91.4)
			Long Range: 85-355 (25.01 - 108.2)
548	550 (500)	966,214 (438 267)	Heavy duty: 79-315 (24-96) Long Range: 138-154 (42.62-108)



TCC-1100



238 HSL